



# KM CLASSIC 3.11

# 9060 0356



## SPECIFICATIONS

POWER RATING	3 KW
MOTOR TURNS	1400 RPM
CURRENT TYPE	1/240/50
FLOW RATE	11 L/MIN
PRESSURE / MAX	100/110 BAR
MAX. TEMPERATURE	110 °C
FUEL COMSUMPTION	4,4 LT/HR
FUEL TANK	18 LT
ANTI-SCALETANK	2,5 LT
DETERGENT TANK	3,5 LT
WEIGHT	120 KG
SIZE	95X62X85
TWO ELECTRIC MOTORS	



access to water filter and pressure adjustment



access to crossbar and tanks filling



water box and softener device



motor for wind fan and fuel pump



triplex pump + banjo valve



## GENERAL FEATURES

- 18-litre capacity fuel tank with level float and fill up filter
- High pressure detergent suction with adjustment, possibility of using an external detergent tank
- Water suction from a tank with an integrated and readily serviceable suction cartridge filter
- Professional 4-pole motor (1400 rpm) with Comet ZW pumps and professional unloader banjo valve VRF-2
- Timed TotalStop
- EASY-START on 1-230 models
- Delayed burner start
- Professional safety valve
- Boiler thermal protection
- Rotary On-Off switch
- Contactor and motor protection with amperometric control
- Temperature setting thermostat
- "No fuel" indicator
- "Machine switched on" indicator
- "Phase control" indicator

PROFESSIONAL USAGE



## ACCESSORIES



GUN GH 301 WITH SWIVEL



700 MM BENT LANCE WITH DETERGENT HEAD



SPRAY NOZZLE 25 045 1/4"



10 MT R1 1/4" H.P. HOSE